

1.4 gal, 1.8 gal, 2.3 gal, 3.5 gal
5.5 L, 7 L, 9 L, 13.5 L

COMPRESSION SPRAYER

Ideal for use in greenhouses, agriculture, landscaping, livestock farming, forestry and pest control.

- Ideal for use under the most demanding conditions thanks to the top quality materials and workmanship used to manufacture the sprayer.
- Multipurpose design makes this sprayer perfect for a variety of formula applications.
- Robust, high output pumping system requires less effort from the operator.
- High-quality materials that are corrosion resistant for long life.
- Large funnel top tank that reduces the risk of spillage when filling.
- Carrying handle and wand clips to make transportation and storage easy.
- Precision adjustable plastic spray nozzle provides spray patterns from fine mist to jet stream.
- Double-braided fiber-reinforced vinyl hose is chemically resistant and flexible.
- Heavy-duty flow control with large filter for trouble-free spraying.
- Padded shoulder strap allows a fatigue-free spraying.
- Minimal maintenance required. Most service can be performed without tools.

*A wide assortment of accessories is available to enhance your spraying performance.

kit that includes:

- Flat fan
- Hollow cone
- Full cone



USED MAINLY FOR:



Insecticides



Herbicides



Disinfectants



Medicinal baths
for husbandry



Fertilizers



TECHNICAL CHARACTERISTICS



Less operator effort for easy pressurization.

The precision nozzle quickly adjusts from mist to stream reducing the time taken to spray.























Hermetic tank lid seal prevents spillage.

Heavy-duty flow control with large filter for trouble free spraying.

One-piece tank prevents leaks. HDPE with UV inhibitor for long life.

Comfort to enhance the operator's when spraying, the tank is ergonomic; the straps are chemically resistant, thick and wide.

ACCESSORIES

Brass spray lances (without spray tip, nut or gasket)  E803-085 - 19.7"/50 cm  E803-400 - 15.7"/40 cm  E219-195-C with two nozzles, length 19.7" / 50 cm		FVR spray lances (without spray tip, nut or gasket)  E219-136-C - 19.7"/50 cm  E219-142-C - 39.4"/1.0 m  E219-143-C - 59.1"/1.50 m  E219-146-C - 78.7"/2.0 m	
Brass extensions (with connector)  E219-500-C - 26.4"/67 cm  E219-510-C - 39.4"/1.0 m  E219-520-C - 47.2"/1.20 m		EXTENSION LANCE: 2-nozzle brass extensions  E219-098-C - 15.74" / 40 cm	
2-nozzle FVR extensions  E219-140-C - 19.6"/50 cm  E219-147-C - 39.37"/20 cm  E219-148-C - 28.7"/73 cm		3-nozzle FVR extensions  E219-138-C - 39.4"-de 1 m  E219-151-C - 59.1 de 1.5 m 3-nozzle brass extensions  E219-420-C - 39.4-1.0 m	
SCREEN SHIELDS  E219-099 - 15.7" / 40 cm  E219-117 - 8.7" / 22 cm		COMPLETE NOZZLES  E803-092-C  E219-610-C  E219-710-C	

TECHNICAL DATA

SPECIFICATIONS	DESCRIPTION			
Model	318195 SP 13	319195 SP 14	320195 SP 15	322195 SP 17
Tank capacity	1.4 GAL / 5.5 L	1.8 GAL / 7 L	2.3 GAL / 9 L	3.5 GAL 13.5 L
Carrying strap	N/A	Padded and adjustable		
Pump ing system	Plastic piston			
Pistón sleeve	1.5" / 38 mm			
Hose	fiber vinyl-reinforced 3/8" ID			
Shut-off valve	Professional ergonomic with filter			

SPECIFICATIONS		DESCRIPTION			
Model	318195 SP 13	319195 SP 14	320195 SP 15	322195 SP 17	
Spray lance Brass	16.5" / 42 cm FVR	20.5" / 52 cm FVR			
Nozzle	Brass Adjustable				
Output per minute at 45 psi(3 bar)	29.8 gal - 880 ml				
Work pressure	1 to 2.5 bar - 14.5 a 36.2 psi				

Due to our commitment to technological progress, we reserve the right to make technical changes without prior notice.

Follow us:



Website: www.swissmex.com

Email: exports@swissmex.com.mx

Telephone: +52 (474) 74 122 16