

Trailed Mill

This equipment was designed and built with the highest technology and the best materials. The most strict quality controls are implemented during its manufacturing process applying very demanding performance and endurance tests to guarantee a long lasting useful life.

- The mill is mounted on a trail axis for an easy transportation.
- Includes a cardan shaft to be powered with tractor's PTO.
- It has two screens: one for stubble and the other for grain. Screens for finer grinding are also available (accessory).
- The two exits of the hopper allow to bag the grinded product in a fast and easy way.
- The power of the mill permits also to take back the hopper and transport the product directly through pipes to silos.

SWISSMEX, remains at the forefront in technology to respond to the requirements of its' customers.



TRAILED MILL TECHNICAL FEATURES.

SPECIFICATIONS	
Suspension	Trailed
Power requirement	25 - 30 HP
Speed	3,200 R.P.M.
Hammers	36 pcs
Length	3.60 m
Width	1.75 m
Height	2.30 m
Weight	462 Kg.
In the interest of continuing the technological advancement, all specifications are subject to change without previous notice.	



SWISSMEX-RAPID, S.A. DE C.V.

☒ P.O. Box 56 & 92 Fax 52/474-7420856
 47400 Lagos de Moreno, “ 52/474-7424185
 Jalisco ☎ 52/474-7420300
 Mexico “ 52/474-7420400
 ventas.exportacion@swissmex.com.mx
 Location: Calle Swissmex No. 500 (Panamerican Hwy. km 445)
 Visit our website www.swissmex.com.mx