

### TRACTOR MOUNTED MILLS

These mills were designed and built using the highest technology and the best materials. The most strict quality controls are implemented during their manufacturing process applying very demanding performance and endurance tests to guarantee a long lasting useful life.

Some of their features are:

- The mills are mounted on the tractor for an easy transportation.
- Include a cardan shaft to be powered with tractor's PTO.
- The mills 610.125 (1.40 m) and 610.135 (1.00 m) have a different feeder height.
- They have two screens: one for stubble and the other for grain. Screens for finer grinding are also available (accessory).
- The two exits of their hoppers allow to bag the grinded product in a fast and easy way.
- The power of the mills permit also to take back the hopper and transport the product directly through pipes to silos.

SWISSMEX remains at the forefront in technology to respond to the requirements of its customers.



## TRACTOR MOUNTED MILLS TECHNICAL FEATURES.

SPECIFICATIONS		
Suspension	3 point hitch	
Tractor type	Category II	
Power requirement	25 - 30 HP	
Speed	3200 R.P.M.	
Hammers	72 pcs.	
Grinding capacity	Up to 2,700 kg/h for grain	
	Up to 1,400 kg/h for stubble	
Length	<b>610.125</b>	<b>610.135</b>
	3.60 m	2.28 m
Width	1.75 m	2.80 m
Height	2.30 m	2.40 m
Weight	440 kg aprox.	
In the interest of continuing the technological advancement, all specifications are subject to change without previous notice.		



## SWISSMEX-RAPID, S.A. DE C.V.

☒ P.O. Box 56 & 92 Fax 52/474-7-42-08-56  
 47400 Lagos de Moreno, " 52/474-7-42-41-85  
 Jalisco ☎ 52/474-7-41-22-00  
 Mexico " 52/474-7-41-22-01  
 ventas.exportacion@swissmex.com.mx  
 Location: Calle Swissmex No. 500  
 Visit our website [www.swissmex.com](http://www.swissmex.com)